



**OTL 35-3X**



**OTL 50-3X**



**OTL 35-5X**

Grey		MAA1335A10	MAA1350A10	-
Grey, Blue, Yellow-green		-	-	MAA5035A10
Yellow-green		-	-	-

**Technical data**

Conductor cross-section Cu, Al (mm <sup>2</sup> )	2,5 - 35	1,5 - 50	2,5 - 35
Nominal voltage AC / DC (V)	1000 / 1500	1000 / 1500	1000 / 1500
Nominal voltage AC / DC (V)	1000	1000	1000
Nominal current (A)	3 x 135 (Cu) / 3 x 120 (Al)	3 x 160 (Cu) / 3 x 145 (Al)	5 x 135 (Cu) / 5 x 120 (Al)
Nominal current (A)	3 x 115 (Cu) / 3 x 90 (Al)	3 x 150 (Cu) / 3 x 120 (Al)	5 x 115 (Cu) / 5 x 90 (Al)
Width / Height / Length (mm)	46 / 40 / 46	49 / 43 / 49	79 / 40 / 65
Screw, hexagonal key	No. 4	No. 5	No. 4
Tightening torque (Nm)	3 Nm (2,5 - 16 mm <sup>2</sup> ) 6 Nm (25 - 35 mm <sup>2</sup> )	1,5 Nm (1,5 - 2,5 mm <sup>2</sup> ) 5 Nm (4 - 10 mm <sup>2</sup> ) 10 Nm (16 - 50 mm <sup>2</sup> )	3 Nm (2,5 - 16 mm <sup>2</sup> ) 6 Nm (25 - 35 mm <sup>2</sup> )
Mounting	DIN rail	DIN rail	DIN rail, screw
Weight (g)	70	81	120
Package (pcs)	20	20	10

**Dimensions**

OTL 35-3X  
OTL 50-3X

OTL 35-5X

