



push-in terminal block 3 levels with earth connection, 2.5mm<sup>2</sup>



Series	EFT
Code	EFTE200
Type	EFTE.2
Colour	Yellow-green
<b>TECHNICAL FEATURES</b>	
Function/Type	3 levels earth terminal blocks
Rated cross-section	2.5 mm <sup>2</sup>
Connecting capacity	
Flexible wire	0.2-4 mm <sup>2</sup>
Rigid wire	0.2-4 mm <sup>2</sup>
Wire with ferrule - ferrule type	2.5 mm <sup>2</sup> - WP25/19
<b>Electrical characteristics according to IEC EN standard</b>	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Caliber	A3
<b>Electrical characteristics according to UL Standard</b>	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	-
Section (min-max)	24-12 (AWG)
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Operating temperature Min/Max	-40 °C / +110 °C
Rated impulse withstand voltage / pollution degree	6 kV / 3
Insulation stripping length	9 mm
Width (pitch)	5.2 mm
Length	106.2 mm
Height mounted on TH35-7.5/TH35-15/G32	68.4 / 75.9 / - mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>End section</b>	
Grey	EFT.2/PT/GR (cod. EFT201GR)
Blue	-
Thickness	1.5 mm
Coloured partition plate	∅
<b>Marking</b>	
Adhesive numbering strip	-
Snap-on numbering strip	-
Single marking tag	CNU/10/51 (cod. NU1051S)
Single marking tag for pitch insertion	CNU/10/51 (cod. NU1051S)
<b>End bracket</b>	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
DIN rail according to IEC 60715/TH35	PR/3/..
<b>APPROVALS AND MARKINGS</b>	Ex, RoHS, REACH, CE, UL, CCC

