

Product data sheet

HLAY5BG25

Characteristics

Key switch, HLAY5, 1 NO + 1 NC, 2 positions 45°, stay put, black



Main

Range of product	HLAY5
Device presentation	Complete product
Product or component type	Key switch
Bezel material	Metal
Mounting diameter	22 mm
Head type	Standard

Complementary

Fixing collar material	Metal
Cap/operator or lens colour	Black
Shape of signaling unit head	Round
Type of operator	Stay put
Operator profile	Key switch
Operator position information	2 positions 45°
Key withdrawal position	Center
Contacts type and composition	1 NO + 1 NC
Contact operation	Slow-break
Contacts usage	Standard contacts
Mechanical durability	100000 cycles
Connections - terminals	Screw clamp terminals
[Ith] conventional free air thermal current	6 A
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	2 A at 380 V 3.3 A at 220 V, AC-15 0.5 A at 220 V 1.1 A at 110 V, DC-13
Electrical durability	50000 cycles
E-commerce address	Hlay5-selector-switches-with-handle

Environment

Ambient air temperature for operation	-5...40 °C
Standards	IEC 60947-5-1

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Offer Sustainability

Sustainable packaging

No
