



Product data sheet

HXCKD003

Characteristics

Limit switch, HXCKD, vertical roller plunger type

	Main	
	Range of product	HXCKD
	Series name	HXC
	Product or component type	Limit switch
	Body type	Fixed
	Body material	Metal
	Head material	Stainless steel
	Fixing mode	By the body
	Movement of operating head	Rotary
	Type of operator	Vertical roller lever
	Cable entry	3 entries tapped for Pg 11.5 cable gland, cable outer diameter: 9...12 mm
	Number of poles	4
	Contacts type and composition	2 x (1 NC + 1 NO)
	Contact operation	Snap action

Complementary

Device presentation	Complete product
Switch actuation	On end
Electrical connection	Screw clamp terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm²
Maximum force for tripping	8 N
Minimum release force	4 N
Maximum pre-travel	1.8 mm
Minimum over travel	4 mm
Maximum movement differential	1.2 mm
Tripping point	2.0 mm
Maximum actuation speed	0.5 m/s
Repeat accuracy	0.1 mm on the tripping points with 1 million operating cycles
Maximum operating rate	30 cyc/mn
[Ithe] conventional enclosed thermal current	10 A AC
[Ui] rated insulation voltage	380 V conforming to IEC 60947-5-1
Maximum resistance across terminals	25 MOhm conforming to IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	2.5 kV conforming to IEC 60947-1
Electrical durability	500000 cycles

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Terminals description ISO n°1	(13-14)NO (11-12)NC
IP degree of protection	IP66
Height	33 mm
Width	113 mm
Depth	62 mm
Product weight	0.199 kg

Environment

Vibration resistance	1.5 mm double amplitude (f= 10...55 Hz)
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Product certifications	CE
Standards	EN 60947-5-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable packaging	No
-----------------------	----